Cosmo Bully SRP Series Power Harrow

The COSMO Bully SRP Series Power Harrows are an economical implement suitable for soil and seed bed preparation on small to medium sized landholdings.

These compact machines are available in working widths from 1.5m to 2.0m and have many of the features of high end models; 120hp rated (540/1000rpm) multi speed gearbox, rear levelling bar and floating side plates.

Cage or packer rollers are also available as an optional extra.

The blade design and rotating action reduces the horsepower requirements of the tractor and results in the ground being worked in fewer passes, even when working at the maximum depth (260mm). This means less soil compaction from the tractor and reduced fuel consumption.





Code	TSRP150	TSRP175	TSRP200
Description	Bully SRP150 Power Harrow	Bully SRP175 Power Harrow	Bully SRP200 Power Harrow
Gearbox	120hp, 540/1000rpm, multi speed		
PT0 shaft/clutch	Series 6 with 200mm (8") friction (slip) clutch		
Rear levelling bar	Manual, mechanical, adjustment		
Side plates	8mm, floating		
Finish	Powder coated		
No. of rotors	6	7	8
Total no. of blades	12	14	16
Blades	285x12mm		
Linkage	Category 2		
Guarding	Standard with CE guards		
Overall width (mm)	1610	1860	2100
Working width (mm)	1500	1750	2000
Working depth (mm)	260		
Tractor range (hp)	50 - 90	60 - 90	70 - 90
Weight (kg)	545	590	640

Options			
Code	TSRP150CR	TSRP175CR	TSRP200CR
Description	Bully SRP150 Cage Roller	Bully SRP175 Cage Roller	Bully SRP200 Cage Roller
Design	Ø385mm, eight (8) bar, mechanical adjustment		
Weight (kg)	76	84	92
Code	TSRP150PR	TSRP175PR	TSRP200PR
Description	Bully SRP150 Packer Roller	Bully SRP175 Packer Roller	Bully SRP200 Packer Roller
Design	Ø420mm with teeth (65mm), scrapers, mechanical adjustment		
Weight (kg)	158	177	196

Parts 7132 7133 SRP blade (right) SRP blade (left)

Cosmo Bully M120 Series Power Harrow

The COSMO Bully M120 Champion Series Power Harrows have been designed and engineered in Europe and are a serious machine for professional operators.

They are robust, with a two piece rigid frame, available in 2.5m and 3.0m widths.

The blade design and action results in soil being finely worked to the maximum depth (280mm) in fewer passes, minimising ground compaction, reducing fuel consumption and placing less load and demands on the tractor.





Options include rear cage or packer rollers (packer rollers shown in photo above) and a quick fit blade system.



Code	TM120/160-250	TM120/160-300	
Description	Bully M120-250 Champion Series Power Harrow	Bully M120-300 Champion Series Power Harrow	
Gearbox	160hp, 540/1000rpm, multi speed		
PTO shaft/clutch	Series W2600 with 200mm (8") friction (slip) clutch		
Rear levelling bar	Manual, mechanical, adjustment		
Side plates	8mm, floating and/or height adjustable		
Finish	Powder coated		
Total no. of blades	20	24	
No. of rotors	10	12	
Rotor speeds	343 - 376 at 540rpm 334 - 369 at 1000rpm		
Blades	285x12mm		
Linkage	Category 2 and 3		
Guarding	Standard with CE guards		
Overall width (mm)	2600	3100	
Working width (mm)	2500	3000	
Working depth (mm)	280		
Tractor range (hp)	100 - 140	120 - 140	
Weight (kg)	850	950	

Options	7,000		
Code	TM120/160-250CR	TM120/160-300CR	
Description	Bully M120-250 Cage Roller	Bully M120-300 Cage Roller	
Design	Ø450mm, eight (8) bar, mechanical adjustment		
Weight (kg)	145	166	
Code	TM120/160-250PR	TM120/160-300PR	
Description	Bully M120-250 Packer Roller	Bully M120-300 Packer Roller	
Design	Ø500mm with teeth (80mm), scrapers, mechanical adjustment		
Weight (kg)	305	360	

M120 Power Harrow blade (right) M120 Power Harrow blade (left) M120 Power Harrow quick fit blade (right) M120 Power Harrow quick fit blade (left)